

## **Under-Cabinet**


Quality construction and ease of installation make the BUEZ2 a popular choice in vertically-ducted economy hoods.

| SIZE   | WHITE ON WHITE | BLACK     | STAINLESS STEEL | NON-DUCT FILTER<br>(replacement) |
|--------|----------------|-----------|-----------------|----------------------------------|
| 30-in. | BUEZ230WW      | BUEZ230BL | BUEZ230SS       | 97006931                         |
| 36-in. | BUEZ236WW      |           |                 | 97006931                         |

| HVI PERFORMANCE  |       |                             |            |                       |  |  |  |  |
|------------------|-------|-----------------------------|------------|-----------------------|--|--|--|--|
| Duct Orientation | Size  | Damper                      | Sones High | CFM High 0.1 in. w.g. |  |  |  |  |
| Vertical - Round | 7-in. | BP87Q (purchase separately) | 6.0        | 190                   |  |  |  |  |

| FEATURES                                                          |                                                                          |  |  |
|-------------------------------------------------------------------|--------------------------------------------------------------------------|--|--|
| Max. Blower CFM*                                                  | 230                                                                      |  |  |
| Control type                                                      | 2-speed Rocker                                                           |  |  |
| Lighting                                                          | 1-level Rocker<br>1- 75W, A19 incandescent bulb<br>(purchase separately) |  |  |
| Fan Blade & Light Lens                                            | Polymeric                                                                |  |  |
| Grease Filter                                                     | 1- Washable aluminum<br>8-3/4" x 10-1/2"                                 |  |  |
| Installation Hardware                                             | EZ1 brackets                                                             |  |  |
| ADA Compatible                                                    | yes                                                                      |  |  |
| AC INPUT                                                          |                                                                          |  |  |
| 120V, 60 Hz - 2.0 AMP                                             | °S                                                                       |  |  |
| OPTIONAL ACCESSO                                                  | RIES                                                                     |  |  |
| ADA Wiring Kit                                                    | HAWRK3                                                                   |  |  |
| MOUNTING HEIGHT                                                   |                                                                          |  |  |
| 18-in. to 24-in. from coo                                         | oktop to bottom of hood                                                  |  |  |
| LIMITED WARRANTY                                                  |                                                                          |  |  |
| 1-year                                                            |                                                                          |  |  |
|                                                                   | com for full warranty text.                                              |  |  |
| FOR INDOOR USE ON                                                 | ILY                                                                      |  |  |
|                                                                   |                                                                          |  |  |
| 0.35                                                              | Vertical High Speed,                                                     |  |  |
| 0.30                                                              | 7-in. round                                                              |  |  |
| ⇒ 0.25                                                            |                                                                          |  |  |
| ej 0.20                                                           |                                                                          |  |  |
| 0.15                                                              |                                                                          |  |  |
| (19) 0.25<br>0.25<br>0.20<br>0.20<br>0.15<br>0.15<br>0.10<br>0.10 |                                                                          |  |  |
| Sta                                                               |                                                                          |  |  |





Can be used to comply with LEED requirements.

100

150

Airflow (cfm)

200

250

300



50

0.10 0.05 0

0

HVI-2100 CERTIFIED RATINGS comply with new testing technologies and procedures prescribed by the Home Ventilating Institute, for off-the-shelf products, as they are available to consumers. Product performance is rated at 0.1 in. static pressure, based on tests conducted in a state-of-the-art test laboratory. Sones are a measure of humanly-perceived loudness, based on laboratory measurements.

\* Max. blower CFM indicates the performance of the hood blower in open air.